






- Mount directly to machine
- Xtreme-Shield™ (NOW standard)
- Rigid Aluminum Backbone, Heatsink
- **NEMA 3S Watertight**
- 16/3 SJTOW 120 VAC Cord
- Anti-Strobe



- Cord Magnetic Mount
- Zero RF Interference
- 5000K Color
- Rated for 50,000 Hours
- Some models ETL, C-ETL Listed



15" & 27" LED DUR-A-LITE:

- 10 Watt Single LED board
- 20 Watt Twin LED boards
- 15" (only) inline power driver

50" LED DUR-A-LITE:

- 20 Watt Dual LED Boards
- 40 Watt Twin-Dual Boards

10" & 41" LED DUR-A-LITE:

- Tough-Shield (only)
- Rigid Aluminum Backbone, Heatsink •
- On/Off Switch

- **Rubber End Caps**
- **Locking Vapor Clamps**
- Rough-Service LED Bulb



3" Diameter LED	Model No.	Description	Tube Type	Watts
	92010-3115	15" LED, Single Board Inline Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	10
	92020-3115	15" LED, Twin Board Inline Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	20
	92010-3515	15" LED, Single Board Inline Driver with 2-10 ft. Coiled + 10 ft. Straight 18/3 SJTOW Cord & Plug	Xtreme-Shield	10
	92020-3515	15" LED, Twin Board Inline Driver with 2-10 ft. Coiled + 10 ft. Straight 18/3 SJTOW Cord & Plug	Xtreme-Shield	20
	92010-3227	27" LED, Single Board, Integrated Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	10
	92020-3227	27" LED, Twin Board, Integrated Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	20
	92020-3250	50" LED, Single Board, Integrated Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	20
	92040-3250	50" LED, Twin Board, Integrated Driver with 25 ft. 16/3 SJTOW Cord & Plug	Xtreme-Shield	40

Xtreme-Shield™

Virtually unbreakable polycarbonate outer tube with a chemical-resistant coating (Standard on 3" diameter models).

Inline Power Driver

Our 15" LED DUR-A-LITE has an external, inline power driver. Available 2 ft.— 10 ft. Coiled Cord + 10 ft. Straight 18/3 Cord.

S	Model No.	Description
Mounts for	5000-1051	Direct Mount
	5000-1052	Magnet Mount, 80#
3″ Di	5000-1053	Bracket Mount
Diameter	5000-1078	Magnet Mount, 110#
er	5000-3000	Metal Magnet Mount



Direct Mount



Magnet Mount



Bracket Mount



Metal Magnet Mount



1	2"	Model No.	Description	Tube Type	Watts
	Diam	91505-2210-10	10" LED DUR-A-LITE with On/Off Switch with 10 ft. 16/3 SJTOW Cord and Plug	Tough-Shield	5.5
	eter	91505-2210-25	10" LED DUR-A-LITE with On/Off Switch with 25 ft. 16/3 SJTOW Cord and Plug	Tough-Shield	5.5
	,	92020-41	41" LED DUR-A-LITE with On/Off Switch with 25 ft. 16/3 SJTOW Cord and Plug	Tough-Shield	12

Mc	Model No.	Description
Mounts	5000-0036	Direct Mount
for	5000-1122	Bracket Mount
· 2" Di	5000-1031	Magnet Mount, 54#
Diameter	1060-3044-1	Flex-Neck Magnet Mount, 54#
ter	1060-8044-1	Flex-Neck Bracket Mount



Direct Mount



Bracket Mount



Magnet Mount



Flex-Neck Magnet Mount



Flex-Neck Bracket Mount